



## MAIN Feature :-

**\* IGBT design with DIGITAL WELDING CURRENT DISPLAY option**

- \* Compact and Portable design with Inverter Technology
- \* Suitable for tradesman, panel beaters, sign writers, refrigeration works etc
- \* Easy starting and excellent arc characteristics with Stainless Steel, Bronze, Aluminium and Cast Iron Electrode up to 5.0mm electrodes
- \* Well Insulated transformer coil to ensure a wide safety against accidentals or overloading
- \* Current Overload Protection

## Technical Data :-

MODEL		WD-150i	WD-200i	WD-220i	WD-250i
Product Code		K202802	K202804	K202806	K202808
Input Voltage	V	240V, 50Hz			
Input Power	KVA	4.9	7	7.9	9.4
No Load Volatge	V	67	67	67	67
Output Load Current	A	20 ~ 150	20 ~ 200	20 ~ 220	20 ~ 250
Output Load Volatge	V	26	28	29	30
Duty Cycle	%	60	60	60	40
Insulation Class		B			
Protection Class		IP 23			
Electrode Size	mm	1.6 ~ 3.2	1.6 ~ 4.0	1.6 ~ 5.0	1.6 ~ 5.0
Weight	KG	8	10	13	15
Dimension (L x W x H)	mm	330 x 140 x 230	420 x 160 x 245	420 x 160 x 245	420 x 160 x 245