

# WeldRo®

Trademark No : 93.07862  
The Symbol Of Quality

## AC - DC ELECTRODE DRYER



A HIGH QUALITY AND DURABLE AC - DC ELECTRODE DRYER OF EPOXY-COATED CASING **THAT LASTS TWICE AS LONG** AS COMPARED TO NORMAL PAINT AGAINST CORROSION TO MEET REQUIREMENTS OF ADVANCED AMERICAN FORMULATION.

**90 Volt DC / 240 Volt AC**  
**Capacity - 5/10 kgs**  
**Electrodes- 450 mm to 500 mm**

If you use low hydrogen electrodes or iron powder-coated or stainless steel, aluminium, inconel, monel, brass, bronze, hard surfacing and other special low alloys, oven protection is not only recommended but mandatory as .....

- All mineral-coated electrodes absorb moisture the minute they are unpacked
- Welding with moist electrode leads to internal and external porosity, underbead weld cracking; rough weld surface, excessive slag fluidity, difficult slag removal and a generally poor appearance
- Proper storage in low temperature holding ovens prevents moisture absorption and unsatisfactory welds.

### Features

- Electrodes can be easily loaded and unloaded
- Small and compact complete with handle - easy to carry around
- Portable type - convenient and easy for the shop or field keeping electrodes warm and dry, within reach of welder
- Even, continuous heat for 100% protection from unpacking to use
- Heating element heats the entire length of the rod chamber - providing faster and more uniform heat distribution



**KIM TAI WELDING SUPPLY SDN BHD - Tel : 603-8062 4777 Fax : 603-8061 6002 E-Mail : kimtai@tm.net.my**  
**Johor Bahru : Tel : 607-353 9711 Penang : Tel : 604-3971258**

Ver : B.06/02 Cat No : K402/1A1